rafeed LED E series

رفيد ليد الفئة أي

BAHR Tri-Proof BH40234

بحر

Bahr tri-proof led fixture for IP65 waterproof, dust, corrosion and pressure-proof.

Maximum efficacy and minimum glare.

Widely used for ambient lighting application.

بحر جهاز انارة مقاوم للماء, الغبار و التآكل بدرجة حماية عالية.

يعطي قدرة عالية من الفعالية و حد ادنى للتوهج.

يستخدم عادة كإنارة منتشرة للعديد من التطبيقات



3 Years Warranty | IP65 | CB | SASO EEL

Power 50 W

Lumen 5000 lm

Input Voltage 220-240 V

Frequency 50/60 Hz

PF 0.9

LED type SMD

Color Temperature 4000

Lumen Efficiency 100 lm/W

Beam Angle 120°

CRI 80

Dimming Method not dimmable

Materials

Color

Dimension (W x L x H) 60 x 1198 x 51 mm

Working temperature -20 C° to +40 C°

Installation way Surface

Applications Supermarkets, Galleries , Parking lots, Airports, Corridors

visit product on website

Luminous flux and connected electrical load are subject to an initial tolerance of +/- %10. Tolerance of color temperature +/- 150 K. Unless stated otherwise, the values apply to an ambient temperature of 25° C.
We reserve the right to make technicale changes without prior notice. Visit us www.rafeed.co