

BAHR Tri-Proof BH60190

بحر

Bahr tri-proof led fixture for IP65 waterproof, dust, corrosion and pressure-proof.

بحر جهاز انارة مقاوم للماء, الغبار و التآكل بدرجة حماية عالية.

Maximum efficacy and minimum glare.

يعطي قدرة عالية من الفعالية و حد أدنى للتوهج.

Widely used for ambient lighting application.

يستخدم عادة كإنارة منتشرة للعديد من التطبيقات


3 Years Warranty

IP65

CB

SASO

EEL




Flux out: 3372 lm

Height	Beam Diameter	Beam Angle
1m	488.4, 15801x	288.35cm
2m	122.1, 395.01x	576.70cm
3m	54.26, 175.51x	865.05cm
4m	30.52, 98.741x	1153.40cm
5m	19.53, 63.191x	1441.75cm
6m	13.57, 43.881x	1730.10cm
7m	9.967, 32.241x	2018.45cm
8m	7.631, 24.691x	2306.80cm
9m	6.029, 19.501x	2595.16cm
10m	4.884, 15.801x	2883.51cm

Height Beam Angle: 110.51deg Diameter

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Power 50 W

Lumen 5000 lm

Input Voltage 220-240 V

Frequency 50/60 Hz

PF 0.9

LED type SMD

Color Temperature 6500

Lumen Efficiency 100 lm/W

Beam Angle 120°

CRI 80

Dimming Method not dimmable

Materials

Color

Dimension (W x L x H) 60 x 1198 x 51 mm

Working temperature -20 C° to +40 C°

Installation way Surface

Applications Supermarkets, Galleries , Parking lots,

Airports, Corridors

visit product on website

