rafeed LED E series

رفيد ليد الفئة أي

DEEM Panel Light DE40401-A

ديم

DEEM LED light panel is designed for residential and commercial suspended grid ceilings.

High efficiency & energy Saving under the condition of the same illumination it saves more than 67% energy compared with the traditional lamp.

3000-6000 CCT.

Easy installation and maintenance, virtually maintenance-free, Ideal for offices, retail, and classrooms.

ديم بانيل لايت مناسبة للأسقف المعلقة السكنية والتجارية.

ذات كفاءة عالية و توفير في حالة الإضاءة فإنها يوفر أكثر من 67٪ من الطاقة مقارنة بالمصباح التقليدي.

3000-6000 CCT.

سهولة التركيب والصيانة ، مثالية للمكاتب ، المحلات التجارية والفصول الدراسية.



3 Years Warranty | IP20

Power 50 W

Lumen 4500 lm

Input Voltage 200-240 V Dedicated driver

Frequency 50/60 Hz

PF 0.5

LED type SMD

Color Temperature 4000

Lumen Efficiency 90 lm/W

Beam Angle 120°

CRI 80

Dimming Method not dimmable

Materials

Color

Dimension (W x L x H) 605 x 605 x 40 mm

Working temperature -20 C° to +40 C°

Installation way Recessed,Push Type

Applications Offices, Hospitals & Clinics, Supermarkets, Schools, Showrooms, Government institutions, Restaurants, Hotel, Galleries , Fashion Stores, Aluminum drop ceiling

visit product on website

Luminous flux and connected electrical load are subject to an initial tolerance of +/- %10. Tolerance of color temperature +/- 150 K. Unless stated otherwise, the values apply to an ambient temperature of 25° C.
We reserve the right to make technicale changes without prior notice. Visit us www.rafeed.co