

DEEM Panel Light DE60402-A

ديم

DEEM LED light panel is designed for residential and commercial suspended grid ceilings.

ديم بانيل لايت مناسبة للأسقف المعلقة السكنية والتجارية.

High efficiency & energy Saving under the condition of the same illumination it saves more than 67% energy compared with the traditional lamp.


ذات كفاءة عالية و توفير في حالة الإضاءة فإنها يوفر أكثر من 67٪ من الطاقة مقارنة بالمصباح التقليدي.

3000-6000 CCT.

CCT 3000-6000

Easy installation and maintenance, virtually maintenance-free, Ideal for offices, retail, and classrooms.

سهولة التركيب والصيانة ، مثالية للمكاتب ، المحلات التجارية والفصول الدراسية.



3 Years
Warranty

IP20

Power 50 W

Lumen 4500 lm

Input Voltage 200-240 V Dedicated driver

Frequency 50/60 Hz

PF 0.5

LED type SMD

Color Temperature 6500

Lumen Efficiency 90 lm/W

Beam Angle 120°

CRI 80

Dimming Method not dimmable

Materials

Color

Dimension (W x L x H) 605 x 605 x 40 mm

Working temperature -20 C° to +40 C°

Installation way Push Type, Surface

Applications Offices, Hospitals & Clinics, Supermarkets, Schools, Showrooms, Government institutions, Restaurants, Hotel, Galleries , Fashion Stores, Aluminum drop ceiling

visit product on website

