

AMIR Down Light AR40249


أمير

AMIR ranges up to 60W, can be used when higher output is needed, for example in retail.

It can be very present, giving that extra touch to a room, ideal to give the space an extra dimension.

يصل أمير حتى 60 واط ويمكن استخدامه عند الحاجة إلى زيادة الإنتاج ، على سبيل المثال في انارة المحلات التجارية.

تأثيره مميز مما يمنح لمسة إضافية للغرفة ، مما يجعله مثاليًا لإعطاء المساحة بُعدًا إضافيًا.




The Average Illuminance Effective Figure

Flux Out: 419-288lm

Height	Avg./Nadir: E	Beam Angle: 50.9°	Diameter / Area
1.0m	288.50 / 953.60lx		0.95m / 0.71sq.m
2.0m	147.12 / 238.41lx		1.90m / 2.85sq.m
3.0m	95.39 / 155.96lx		2.86m / 6.41sq.m
4.0m	71.78 / 116.97lx		3.81m / 11.40sq.m
5.0m	58.11 / 95.18lx		4.76m / 17.81sq.m
6.0m	49.25 / 79.49lx		5.71m / 25.65sq.m
8.0m	36.50 / 59.90lx		7.62m / 45.60sq.m
9.0m	32.22 / 52.77lx		8.57m / 57.1sq.m
10.0m	28.88 / 46.44lx		9.52m / 71.25sq.m
12.0m	20.99 / 34.22lx		11.43m / 102.60sq.m

Luminous Intensity Distribution Curve



5 Years
Warranty

IP20

Power 8 W

Lumen 600 lm

Input Voltage 220-240 V

Frequency 50/60 Hz

PF 0.5

LED type COB

LED By CREE

Color Temperature 4000

Lumen Efficiency 75 lm/W

Beam Angle 50°

CRI 80

Dimming Method not dimmable

Materials

Color

Dimension (D x H) 90 x 50 mm

Cut Out 75 mm

Working temperature -20 C° to +40 C°

Installation way Recessed

Applications Offices, Hospitals & Clinics, Supermarkets, Schools, Showrooms, Government institutions, Restaurants, Hotel, Fashion Stores

visit product on website

