rafeed LED E series

رفيد ليد الفئة أي

LANA Recessed Panel Downlight LA30043

لانا

This fixture can be used in stores and malls, in addition to villas and luxurious apartments, as it distributes the light in an organized way and gives a nice view.

يستخدم هذا الجهاز في الفنادق، المشافي، المطاعم، المؤسسات الحكومية وصالات العرض، بالإضافة إلى انه يستخدم في المحلات التجارية والأسواق التجارية ويمكن إستخدامه في الفلل والشقق السكنية الفخمة حيث يقوم بتوزيع الإنارة بشكل منتظم ويعطي منظرا جميلا.



2 Years Warranty | IP20 | CCC

Power 3 W

Lumen 203 lm

Input Voltage 200-240 V

Frequency 50/60 Hz

PF 0.5

LED type SMD

Color Temperature 3000

Lumen Efficiency 67 lm/W

Beam Angle 120°

CRI 70

Dimming Method not dimmable

Materials

Color

Dimension (D x H) 85 x 14.5 mm

Cut Out 60 mm

Working temperature -20 C° to +40 C°

Installation way Recessed

Applications Hospitals & Clinics, Restaurants, Showrooms, Supermarkets, Hotel, Offices, Government institutions, Schools

visit product on website

Luminous flux and connected electrical load are subject to an initial tolerance of +/- %10. Tolerance of color temperature +/- 150 K. Unless stated otherwise, the values apply to an ambient temperature of 25° C.
We reserve the right to make technicale changes without prior notice. Visit us www.rafeed.co